

G-Series

Selection and ordering data for side channel blowers in vacuum and pressure operation.

	HZ	KW	V	A	kg	dB(A)	m ³ /h	mbar	mbar	
• 2RB 910-7AH07	50	8.5	345-415 △ /600-720	18.2 △ /10.5Y	93	74	1050	-210	210	1×...750/...860
	60	9.8	380-480 △ /660-720	18.2 △ /10.5Y		79	1250	-180	180	1×...754/...864
• 2RB 910-7AH17	50	12.5	345-415 △ /600-720	28.0 △ /16.2Y	116	74	1050	-280	270	1×...750/...860
	60	14.5	380-480 △ /660-720	29.0 △ /16.7Y		79	1250	-270	260	1×...754/...864
• 2RB 910-7AH37	50	18.5	345-415 △ /600-720	37.0 △ /21.0Y	126	74	1050	-340	460	1×...750/...860
	60	21.3	380-480 △ /660-720	39.0 △ /22.5Y		79	1250	-380	420	1×...754/...864
• 2RB 920-7HH17	50	12.5	345-415 △ /600-720	28.0 △ /16.2Y	187	74	1110	-300	270	1×...750/...860
	60	14.5	380-480 △ /660-720	29.0 △ /16.7Y		78	1310	-220	200	1×...754/...864
• 2RB 920-7HH27	50	16.5	345-415 △ /600-720	35.0 △ /20.0Y	197	74	1110	-410	370	1×...750/...860
	60	19.0	380-480 △ /660-720	36.5 △ /21.0Y		78	1310	-340	300	1×...754/...864
• 2RB 920-7HH37	50	20.0	345-415 △ /600-720	40.0 △ /23.0Y	204	74	1110	-440	500	1×...750/...860
	60	23.0	380-480 △ /660-720	42.0 △ /24.2Y		78	1310	-440	430	1×...754/...864
• 2RB 920-7HH47	50	25.0	345-415 △ /600-720	52.0 △ /30.0Y	211	74	1110	-440	590	1×...750/...860
	60	29.0	380-480 △ /660-720	52.0 △ /30.0Y		78	1310	-440	540	1×...754/...864
• 2RB 930-7AH07	50	8.5	345-415 △ /600-720	18.2 △ /10.5Y	98	75	1370	-120	110	2×...750/1×...880
	60	9.8	380-480 △ /660-720	18.2 △ /10.5Y		80	1650	-80	70	2×...754/1×...864
• 2RB 930-7AH17	50	12.5	345-415 △ /600-720	28.0 △ /16.2Y	121	75	1370	-210	190	1×...750/...880
	60	14.5	380-480 △ /660-720	29.0 △ /16.7Y		80	1650	-170	160	1×...754/...864
• 2RB 930-7AH37	50	18.5	345-415 △ /600-720	37.0 △ /21.0Y	131	75	1370	-310	320	1×...750/...880
	60	21.3	380-480 △ /660-720	39.0 △ /22.5Y		80	1650	-300	280	1×...754/...864
• 2RB 940-7BH27	50	15.0	345-415 △ /600-720	35.0 △ /20.0Y	187	75	1940	-130	110	2×...750/1×...880
	60	17.5	380-480 △ /660-720	36.5 △ /21.0Y		84	2310	-60	40	2×...754/1×...864
• 2RB 940-7BH37	50	20.0	345-415 △ /600-720	40.0 △ /23.0Y	212	75	1940	-220	200	2×...750/1×...880
	60	23.0	380-480 △ /660-720	42.0 △ /24.2Y		84	2310	-160	130	2×...754/1×...864
• 2RB 940-7BH47	50	25.0	345-415 △ /600-720	52.0 △ /30.0Y	219	75	1940	-310	270	1×...750/...880
	60	29.0	380-480 △ /660-720	52.0 △ /30.0Y		84	2310	-270	220	1×...754/...864
• 2RB 943-7BH27 ⁽¹⁾	50	15.0	345-415 △ /600-720	35.0 △ /20.0Y	220	75	2050	-160	170	2×...750/1×...870
	60	17.5	380-480 △ /660-720	36.5 △ /21.0Y		84	2480	-110	120	2×...754/1×...874
• 2RB 943-7BH37 ⁽¹⁾	50	20.0	345-415 △ /600-720	40.0 △ /23.0Y	230	75	2050	-250	230	2×...750/1×...870
	60	23.0	380-480 △ /660-720	42.0 △ /24.2Y		84	2480	-190	180	2×...754/1×...874
• 2RB 943-7BH47 ⁽¹⁾	50	25.0	345-415 △ /600-720	52.0 △ /30.0Y	235	75	2050	-310	270	2×...750/1×...870
	60	29.0	380-480 △ /660-720	52.0 △ /30.0Y		84	2480	-270	230	2×...754/1×...874

·mounting on the end-casing only

